




# PEDESTRIAN VS. VEHICULAR USAGE COMPARISON

		 PEDESTRIAN USE	 LIGHT VEHICULAR USE**	 MODERATE VEHICULAR USE**
		use by persons on foot and any mobility impaired persons using a wheelchair	pedestrian use & low speed, low volume residential and light commercial vehicular use	pedestrian use & low speed, moderate volume residential and moderate commercial vehicular use
	HANOVER® PRODUCT	MINIMUM THICKNESS	MINIMUM THICKNESS	MINIMUM THICKNESS
PREST® BRICK	Riven	3"	3"	3"
	Olde Hanover®	2 3/8"	2 3/8"	NO MODERATE VEHICULAR USE
	Serengeti® 6" x 6" & 6" x 9"	2 3/8"	2 3/8"	NO MODERATE VEHICULAR USE
	Serengeti® Mixed	3"	3"	3"
	Serengeti 14" x 14"	3"	3"	NO MODERATE VEHICULAR USE
	Halifax® Flagstone	3"	3"	3"
	Appian®	2 3/8"	2 3/8"	3"
	PlankStone®	4"	PLANKSTONE® 3" x 9" x 4" ONLY	PLANKSTONE® 3" x 9" x 4" ONLY
	Traditional®	2 3/8"	2 3/8"	3"
	Multisided	2 3/8"	2 3/8"	3"
	Hampshire™	3"	3"	NO MODERATE VEHICULAR USE
	Parallelogram	3"	3"	NO MODERATE VEHICULAR USE
Appalachia	3"	3"	NO MODERATE VEHICULAR USE	
PERMEABLE PAVING UNITS	Aqua-Loc®	3"	3"	3"
	EcoGrid®	4"	4"	NO MODERATE VEHICULAR USE
	Permeable 4" x 8"	3"	3"	3"
	Permeable 4 1/2" x 9"	3"	3"	3"
	Permeable 4 1/2" x 9" Scored	3"	3"	3"
	Permeable 3 1/4" x 18"	4"	NO LIGHT VEHICULAR USE	NO MODERATE VEHICULAR USE
Permeable 12" x 18"	3"	NO LIGHT VEHICULAR USE	NO MODERATE VEHICULAR USE	
PREST® PAVERS	11 3/4" x 11 3/4"	2" <small>All Prest® Paver sizes are applicable for pedestrian use at a 2" or greater thickness.</small>	3" *	NO MODERATE VEHICULAR USE
ASPHALT BLOCK	4" x 6", 6" x 6", 5" x 12" 6" x 12", 8" x 8" 8" Hexagonal	1 1/4"	3"	3"
	3D Diamond	1 1/4"	NO LIGHT VEHICULAR USE	NO MODERATE VEHICULAR USE
CHAPEL STONE® PAVERS	6" x 12" approximately	4"	4"	4"

\* The 11 3/4" x 11 3/4" x 3" Prest® Paver is applicable only in limited vehicular conditions. Please contact Hanover® Technical Sales Staff for more information.

\*\* Hanover® recommends 45° and 90° Herringbone installation designs when unit paver dimensions permit. Herringbone designs are fully interlocked and resist vehicular load forces.

For vehicular applications, base materials must be engineered with the intended vehicular loading conditions in mind. Please contact Hanover® Technical Sales Staff for more information. • Hanover® suggests, Prest® Pavers for urban environments have a thickness of 2 1/2". • Please Note: Not all sizes/colors are stocked materials. Some are only available through special order and when quantities permit. • Not all product styles are available in the full range of thicknesses. Please refer to Hanover's specific product information for availability.


  
**HANOVER®**  
**Architectural Products**  
 5000 Hanover Road, Hanover, PA 17331  
 717.637.0500 fax 717.637.7145  
[www.hanoverpavers.com](http://www.hanoverpavers.com)