

100% Asbestos Free

HANOVER[®] PAVER MASTIC

Used for adhering brick or block in paving applications

VOC Content < 150 g/l

2% Neoprene Modified

Description

Paver Mastic is a high quality modified asphalt mastic designed expressly as an adhesive for bricks and pavers.

Coverage

30 - 50 square feet per gallon (150 - 250 square feet per pail)

Net Contents

5 US Gallons (18.925 L)

Application

Paver Mastic must be applied to surface free of all foreign matter. Paver Mastic should be applied as a skim coat to a 1/16" maximum with a straight edge trowel or squeegee. Allow mastic to flash off but not dry before embedding pavers. Paver Mastic should yield a coverage rate of 30 - 50 sq. ft. per gallon. This material may bleed or seep through block joints if the mastic is applied too heavily. For best results, the temperature is recommended to be above 70°F, although Paver Mastic can be applied at any temperature. Cold Weather Application: Cold temperatures will increase the viscosity of the Paver Mastic. Care must be taken in troweling the product to make sure a paper thin 1/16" skim coat is maintained. This may require the product be brought to a more ambient temperature, making the Paver Mastic more pliable. At all costs, a 1/16" maximum thickness must be satisfied.

For complete application instructions, refer to product label.

Before using this product, read the Safety Data Sheet for additional safety precautions.

To request a Safety Data Sheet, call 800.426.4242 or visit www.hanoverpavers.com.

Cautions

COMBUSTIBLE! DO NOT use or store near flames, sparks or heat. Harmful to eyes and skin. DO NOT get in eyes, on skin, or in clothing. Wear goggles, gloves and protective clothing when handling product. DO NOT breathe vapors or fumes. For outdoor use only. Keep out of sewers and water courses and advise authorities if unable to do so.

HANOVER[®]
Architectural Products
5000 Hanover Road, Hanover, PA 17331
717.637.0500 • fax 717.637.7145
www.hanoverpavers.com