



PAINT, TAR and RUBBER REMOVER for PAVERS

(60100780 / 1 L)

UPDATE

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com
 Canada and U.S.A.: dial 1 800 465-7325
 Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Pavers, slabs concrete and masonry.

PROPERTIES

- Water-Rinsable

DESCRIPTION

Techniseal® Paint, Tar and Rubber Remover effectively dissolves paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry.

DIRECTIONS

BEFORE YOU BEGIN

- Wear adequate protective clothing. • **ALWAYS TEST** on a small hidden stain to ensure the results will meet your expectations. • Surface should, ideally, be dry and warm to the touch.

APPLICATION

Cover stain generously with Remover; let work for 5 to 10 minutes. Reapply product and, using a small nylon scrub brush, scrub until stain is dissolved. Do not let dry; rinse immediately.

NOTE: This product dissolves any sealant; apply a new coat of sealant on stripped surface.

PACKAGING

Product code	Size	Units per box	Units per pallet
60100780 (241-541)	1 L	6	480

WARNING

CONTENTS HARMFUL MAY IRRITATE EYES MAY IRRITATE SKIN Do not swallow. Do not get in eyes. Do not get on skin or clothing. Keep away from flames or sparks. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection. **FIRST AID TREATMENT Contains:** Solvent naphtha (petroleum), light arom.; 1,2,4-Trimethylbenzene; N-Methyl-2-pyrrolidone; Dimethyl glutarate; Dimethyl adipate; Acetone; Glycols, polyethylene, Mono(p-(1,1,3,3-tetramethylbutyl)phenyl) ether If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

EMERGENCY PHONE : CANUTEC (613) 996-6666. SEE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT

SHIPPING

Land

Exempted under the regulation of the transport of hazardous materials (see section 1.33).

Packaging class III (flash point > 37,8 °C)

Sea

Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene)

UN1993

Flammable liquids, n.o.s. (1,2, 4-trimethylbenzene)

Class: 3

PG: III

LIMITED WARRANTY

Techniseal® warrants this Remover against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim.