



PROFESSIONAL GRADE OIL & GREASE REMOVER for PAVERS

(60300025 / 1 qt.)

UPDATE

April 23, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com
U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Sealed or bare surfaces
- Pavers and slabs made of concrete or natural stone, poured or stamped concrete, masonry, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Removes penetrated petroleum-based products
- Clean - dries from a liquid to a powder

DESCRIPTION

Techniseal® Professional Grade Oil & Grease Remover is an industrial strength oil and grease remover. It lifts and absorbs embedded oil and grease stains as it dries from a liquid to a powder. Specially formulated for concrete pavers, slabs and walls, natural stone, poured or stamped concrete, etc., Techniseal® Professional Grade Oil & Grease Remover works without damaging or discoloring the material and is easy to use.

DIRECTIONS

Important: Wear adequate protective clothing. To ensure the results will meet your expectations, **ALWAYS TEST** the product on a small hidden area. Do not use on asphalt. For best results, use when temperature is between 60 and 75°F and provide maximum ventilation. During hot summer days, apply product in the evening and let work overnight.

APPLICATION

Shake well. Apply a generous amount of product to an oil or grease stain and let sit until product has turned to powder. With temperature above 60°F and good ventilation, this process should take between 5 and 8 hours. Process is slowed down and may be inhibited in lower temperatures. When the product has completely dried to a powder, sweep up with a broom and dispose of the powder. **Note:** Surface may still appear dark immediately after powder is swept up. This is not oil but rather a citrus-based solvent that should evaporate within a few hours or days. **Note:** This product will dissolve sealants.

STORAGE AND SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product’s shelf life is at least 2 years following production (see date on packaging).

PACKAGING

Product Code	Retail Size	Units per box	Boxes per pallet
60300025 (121-591)	1 qt.	6	600

WARNING



PROFESSIONAL GRADE OIL & GREASE REMOVER for PAVERS

DANGER

Flammable liquid and vapor.
 Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 Read label before use. KEEP OUT OF REACH OF CHILDREN. If medical advice is needed, have product container or label at hand.
 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 100%
 Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use

only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Store locked up.

Store in a well-ventilated place.

Keep cool.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Max VOC: less than 4%

Techniseal®, 300 Liberté, Candiac (Québec), Canada J5R 6X1

SHIPPING

Land and sea: Regulated

Flammable liquid

UN 1993, Class 3

Packing Group: III

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal® can not guarantee the results. Techniseal warranty is limited to the replacement of product. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.